



**KINGKRETE**  
We Create Future

KingKrete · Flooring Systems  
Epoxy Resin Flooring

# KingFloor® EP400 System

Solvent free high build epoxy floor coating for 200 to 400 microns thickness


KingFloor Primer | KingFloor Primer S | KingFloor EP400

<b>Manufacturer</b>	KingKrete	<b>Resin Base</b>	Epoxy
<b>System Reference</b>	FL-EP-EP400	<b>No. of Layers</b>	3
<b>System Type</b>	Solvent free high build epoxy floor coating for 200 to 400 microns thickness		
<b>Document</b>	System Information Sheet · Issue 01.2026 · V1.0		

## 1. SYSTEM OVERVIEW

KingFloor EP400 is a high build, hard wearing, solvent free epoxy resin coating, designed to provide a hard and glossy coating to concrete floors. It is supplied as a coloured base (resin) and hardener in pre-weighted quantities ready for onsite mixing and use. KingFloor EP400 permits the application of floor coatings at 200 - 400 microns per coat and can be supplied in different colours to suit the site requirements.

## 2. SYSTEM BUILD-UP



NO.	COMPONENT / LAYER	FUNCTION
1	KingFloor Primer	Primer / bonding coat
2	KingFloor Primer S	Primer / bonding coat
3	KingFloor EP400	Epoxy floor coating
-	Concrete substrate	Prepared base (shot-blast / grind)

Indicative system cross-section

## 3. TYPICAL APPLICATIONS

- rf: Aircraft hangars
- rf: Car parks
- rf: Soft drink and beverage production areas
- rf: Dairies production areas
- rf: Show rooms
- rf: Production, maintenance and assembly areas
- rf: Warehouses
- rf: General food processing and manufacturing plants

System overview and applications summarised from the individual product Technical Data Sheets (TDS). Refer to the relevant KingKrete product TDS and Safety Data Sheets for complete specifications, mixing, coverage and application details.

