



KINGKRETE
We Create Future

KingKrete · Flooring Systems
Epoxy Resin Flooring

KingFloor® EP75 System

Solvent free high build epoxy floor coating for thickness up to 200 microns in one coat


KingFloor Primer | KingFloor Primer S | KingFloor EP75

Manufacturer	KingKrete	Resin Base	Epoxy
System Reference	FL-EP-EP75	No. of Layers	3
System Type	Solvent free high build epoxy floor coating for thickness up to 200 microns in one coat		
Document	System Information Sheet · Issue 01.2026 · V1.0		

1. SYSTEM OVERVIEW

KingFloor EP75 is a high build, hard wearing, solvent free epoxy resin coating, designed to provide a hard, gloss coating to concrete floors. It is supplied as base (resin) and hardener in addition to a colour pack which contains reactive ingredients in preweighed quantities ready for on site mixing and use. KingFloor EP75 permits the application of floor coatings of 200 microns per coat and can be coloured to suit site requirements.

2. SYSTEM BUILD-UP



NO.	COMPONENT / LAYER	FUNCTION
1	KingFloor Primer	Primer / bonding coat
2	KingFloor Primer S	Primer / bonding coat
3	KingFloor EP75	Epoxy floor coating
-	Concrete substrate	Prepared base (shot-blast / grind)

Indicative system cross-section

3. TYPICAL APPLICATIONS

- rf: Aircraft hangars
- rf: Car parks
- rf: Soft drink and beverage production areas
- rf: Dairies production areas
- rf: Show rooms
- rf: Production, maintenance and assembly areas
- rf: Warehouses
- rf: General food processing and manufacturing plants

System overview and applications summarised from the individual product Technical Data Sheets (TDS). Refer to the relevant KingKrete product TDS and Safety Data Sheets for complete specifications, mixing, coverage and application details.

