

# KingMix® 1050SP

High range water reducing Superplasticiser admixture especially designed for Pre-cast concrete.

## DESCRIPTION

KingMix 1050SP is superplasticising admixture formulated from selected polymers specially designed to enable the water content of the concrete to perform more effectively with higher developed early strength, this effect can be used to improve workability, to increase ultimate strengths or to facilitate a reduction in the cement content while sustaining mix properties. KingMix 1050SP is chloride free.

## APPLICATIONS

KingMix 1050SP is recommended for use in conditions such as:

- ☐ Low water cements ratios.
- ☐ To produce high quality concrete of improved durability and water tightness.
- ☐ Pre-cast concrete.
- ☐ Early concrete strength requirements.
- ☐ High strength concrete.

## ADVANTAGES

KingMix 1050SP provides for the following:

- ☐ Improved workability without increased water content.
- ☐ High reduction in water without loss of workability.
- ☐ Improved early and long term strengths.
- ☐ Chloride free - does not attack reinforcement.

## COMPATIBILITY

KingMix 1050SP is compatible with other KINGKRETE admixtures used in the same concrete mix.

If more than one type of admixture will be used in concrete mix, they must be dispensed to the concrete separately.

## STANDARDS

KingMix 1050SP complies with the following specifications:

- ☐ EN934-2.
- ☐ BS5075.
- ☐ ASTM C494, Type C and E.

## METHOD OF USE

KingMix 1050SP can be added to the mixing water prior to its addition to the concrete mix, or dispensed separately after the addition on mixing water.

## TECHNICAL PROPERTIES

Colour:	Brown liquid
Freezing point:	-8°C
Specific gravity:	1.24 ± 0.01
Chloride content: BS5075	Nil
Air entrainment:	Typically less than 2% additional air is entrained above control mix at normal dosages

## DOSAGE

Dosage of KingMix 1050SP will vary depending on cement content and outside temperature. Required dosage should be determined for each case.

Typical dosage is between 1 - 3% of cement content. Dosages outside the typical range given above may be used to meet particular requirements.

## CLEANING

KingMix 1050SP spillage should be collected by suitable absorbent like sand or vermiculite and transfer by suitable container.

KingMix 1050SP should not be allowed to enter sewers or open bodies of water.

Dispose of in accordance with local environmental regulations.

## PACKAGING

KingMix 1050SP is available in 25 and 210 liters drums, and 1000 liters containers.

## STORAGE

Shelf life is 1 year when stored under cover, out of direct sunlight and protected from extremes of temperature.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult KingKrete's Technical Services Department.

## HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Reseal containers after use. Use in well ventilated areas and avoid inhalation.



# KingMix® 1050SP

High range water reducing Superplasticiser admixture especially designed for Pre-cast concrete.

## NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local KingKrete representative. KingKrete Inc. reserves the right to have the true cause of any difficulty determined by accepted test methods.

## QUALITY AND CARE

All products originating from KingKrete's Middle East facility are manufactured under a management system independently certified to conform to the requirements of the quality standards ISO 9001, ISO 14001 and ISO 45001.

\* Properties listed are based on laboratory-controlled tests.  
® = Registered trademark of the KingKrete-Group in many countries.

Ref: KK-01047-MEA-R01 | Issue: 01.2026

## STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this KingKrete Inc. publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

## NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by KingKrete Inc. either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not KingKrete Inc. are responsible for carrying out procedures appropriate to a specific application.

KingKrete Middle East  
Qatar – Syria  
[www.kingkrete.com](http://www.kingkrete.com)

Disclaimer: the IAS mark relates to certified management system and not to the product mentioned on this datasheet

